

# ML SERIES

## SYSTEM SPECIFICATIONS

### Dimensions:

**ML-22**  
27 $\frac{1}{4}$ " L x 27 $\frac{1}{4}$ " w x 53" H

**ML-24**  
50" L x 27 $\frac{1}{4}$ " w x 53" H

**ML-26**  
72" L x 27 $\frac{1}{4}$ " w x 53" H

**ML-44**  
50" L x 50" w x 53" H

**ML-46**  
72" L x 50" w x 53" H

### Shipping Weight

**ML-22**  
400 lbs.

**ML-24**  
650 lbs.

**ML-26**  
800 lbs.

**ML-44**  
1125 lbs.

**ML-46**  
900 lbs. + 500 lbs.

### Capacity:

**ML-22**  
50 gallons

**ML-24**  
110 gallons

**ML-26**  
150 gallons

**ML-44**  
230 gallons

**ML-46**  
330 gallons

### Recommended Load:

**ML-22**  
30 lbs. of lobster

**ML-24**  
75-100 lbs. of lobster  
35 lbs. of trout  
50-60 lbs. of catfish

**ML-26**  
100-125 lbs. of lobster  
50 lbs. of trout  
70-80 lbs. of catfish

**ML-44**  
150-200 lbs. of lobster  
70 lbs. of trout  
100-110 lbs. of catfish

**ML-46**  
200-250 lbs. of lobster  
100 lbs. of trout  
150 lbs. of catfish

### Power Requirements:

**ML-22, ML-24, ML-26**  
15 AMPS, 115V, 60 Hz

**ML-44**  
20 AMPS, 115V, 60 Hz

**ML-46**  
30 AMPS, 115V, 60 Hz

### Filtration:

#### Mechanical Filtration:

Two (Upper and Lower)  
Polyfiber Filter Pads

#### Chemical Filtration:

Black Diamond Premium  
Activated Carbon

#### Biological Filtration:

Biological Filter Material #1  
Biological Filter Material #2  
Marineland Beneficial  
Bacteria (Liquid)

### Refrigeration:

Fractional Horsepower  
Compressor with Helical  
Heat Exchanger

### Installation Connections:

**Electric Supply:**  
115 VAC., 60 Hz, 15 AMP

**Recommendation:**  
20 AMP Dedicated Circuit

**Sump Drain:**  
3/4" Flexible Tubing